

**Sections:****14-101 Application****14-102 Modification of Height Regulations****14-103 Modification of Area Regulations**

**14-101 Application:** The regulations set forth in this Article qualify or supplement the district regulations appearing elsewhere in these Regulations.

**14-102 Modification of Height Regulations:**

1. The height regulations as prescribed in these Regulations shall not apply to the following buildings or structures where permitted by these regulations:

- Agricultural Buildings and Structures
- Belfries
- Chimneys
- Church Spires
- Communication Tower
- Conveyors
- Cooling Towers
- Elevator Penthouses
- Fire Towers
- Flag Poles
- Grain Elevators
- Lighting Poles or Standards
- Monuments
- Ornamental Towers and Spires
- Small Wind Energy Conversion Systems
- Smoke Stacks
- Stage Towers or Scenery Lofts
- Tanks
- Water Towers

Provided, however, that the setbacks of the structures from all lot lines are equal to the height of the structures. The height restrictions imposed apply to uses allowed by right only. Uses that require a Conditional Use Permit address height issues relative to the approval process.

2. Public or semi-public service buildings, hospitals, institutions, or schools, when permitted, may be erected to a height not exceeding 75 feet, when the required side and rear yards are increased by at least 1 foot for each 1 foot of additional building height above the height regulations for the district in which the building is located.

**14-103 Modification of Area Regulations:****1. Yards, generally:**

- A. Except as herein provided for accessory buildings and structures, whenever a lot abuts upon a public alley, one-half of the alley width may be considered as a portion of the required yard.

- B. Every part of a required yard shall be open to the sky, except as authorized by this Article. Ordinary projections of sills, awnings, canopies, belt courses, air conditioning units, chimneys, cornices, and ornamental features may project to a distance not to exceed 24 inches into a required yard setback.
- C. In the event that a lot is to be occupied by a group of two or more related buildings to be used for residential, school, institutional, hotel, or motel purposes, there may be more than one main building on the lot where such buildings are arranged around a court having a direct street access; provided, however:
  - (1) That said court, between buildings that are parallel or within 45 degrees of being parallel, shall have a minimum width of 30 feet for 1-story buildings, 40 feet for 2-story buildings, and 50 feet for 3-story buildings, and, in no case may such buildings be closer to each other than 15 feet;
  - (2) Where a court having direct street access is more than 50 percent surrounded by a building, the minimum width of the court shall be at least 20 feet for 1-story buildings, 30 feet for 2-story buildings, and 40 feet for 3-story buildings.
- D. Where a lot is used for a commercial or industrial purpose, more than one main building may be located on the lot, but only when such buildings conform to all open space requirements on the lot.

## 2. **Accessory Buildings and Structures:**

- A. Except as herein provided, no accessory building shall project into a required yard setback along any street.
- B. Filling station pumps and pump islands may occupy the required yards; provided, however, that they are not less than 15 feet from the property line, and further provided that canopies and other similar coverings over the pumps and pump islands shall have at least 14 feet of vertical clearance and shall not project beyond the property line.
- C. Accessory storm caves which are not a part of the main building may occupy a required rear yard, provided they are not located closer than 5 feet to the side or rear lot line. No alley may be used in meeting this requirement.

## 3. **Front Yards:**

- A. When an official line has been established for the future widening or opening of a public street or road upon which a lot abuts, then the depth of a front or side yard shall be measured from such official line to the nearest line of the building.
- B. On double frontage lots, the required front yard shall be provided on each street frontage.
- C. Open, unenclosed porches, platforms, or paved terraces, not covered by a roof or canopy and which extend or project into the front and side yard shall not extend or project into the required front yard more than 10 feet or into the required side yard more than 6 feet.

4. **Easements:** No building, either a main or an accessory building, shall be constructed, moved, or altered so as to encroach onto or within a platted or recorded easement.